

iAGE520ES-PM

Tower 5-bay eSATA Port Multiplier Enclosure



INTRODUCTION

iAGE520ES-PM is a five Bay Hot-Swap Serial ATA (SATA) Port Multiplier Enclosure. It provides users a low cost and high performance external data backup solution. The convenience of eSATA Port Multiplier 1:5 solution brings users an easy installation and a fast data transmission experience.

FEATURES

- Supports SATA (3Gbps)
- Aluminum Housing, Anodized Surface, Benefits for Cooling and Durability
- Port Multiplier for Five Removable SATA Drive Trays
- Built-in Fans for Self-Contained Ventilation
- Individual Key Lock of Each HDD Tray for Physical Security
- LED Indicators for Power and Activity on Each HDD Tray
- Environmental Monitoring with Power/FAN/TEMP LEDs and Mutable Buzzer Alarm

iAGE520ES-PM

SPECIFICATION

Host Interface	SATAII (one eSATA connector)
HDD Interface	SATA I/II
Data Transfer Rate	SATA 1.5/3 Gbps
Hot-Swap	Both on Host and Device
Tray LED Display	Green – Power on indicator; Blue – Busy (HDD Accessing) indicator
LED Display for Environmental Monitoring	POWER on LED - white FAN normal – green; fail – red (too slow rpm or stop) TEMP normal – green; over 55°C – red
Dimension LxWxH (cm)	23.15 x 15.68 x 20.97 cm
Material	Anodized Aluminum with Mirror Acrylic plastic front panel & Plastic Tray Face
Power Supply	150W (High reliability of IPC form-factor) Input: 90 – 230 VAC 50- 60 Hz Output: +5V and +12V DC
Cooling	Two 70 x 70 x 10 mm Cooling Fans
System Requirement	SiI3132 PCI-Express / ExpressCard or SiI3124 PCI-X Host Bus Adapter with eSATA connector
O.S. Support	OS Independant



PACKAGE CONTENT

- Enclosure x 1
- HDD Tray x 5
- eSATA Cable x 1
- Power Cord x 1
- Manual CD-ROM x1
- Hard Disk Drive mounting screw x 20
- Key for HDD tray x 2