





DIMENSION		
NO.	TYPE	WIRE
20P+4P		
1	500±20mm	16#
HDD 4P *2		
1	500±20mm	18#
2,3	150±10mm	18#
4	150±10mm	22#
SATA 5P		
1	500±20mm	18#
2	150±10mm	18#
CPU 4P(P12V2)		
1	500±20mm	18#

HDD 4P			
PIN	COLOR	VOLTAGE	DC
1	YELLOW	+12V1	
2	BLACK	GND	
3	BLACK	GND	
4	RED	+5V	
FLOPPY 4P			
1	YELLOW	+12V1	
2	BLACK	GND	
3	BLACK	GND	
4	RED	+5V	
SATA 5P			
1	YELLOW	+12V1	
2	BLACK	GND	
3	RED	+5V	
4	BLACK	GND	
5	ORANGE	+3.3V	
CPU 4P			
1	BLACK	GND	
2	BLACK	GND	
3	YEL/BLK	+12V2	
4	YEL/BLK	+12V2	

24P			
PIN	COLOR	VOLTAGE	DC
1	ORANGE	+3.3V	
2	ORANGE	+3.3V	
3	BLACK	GND	
4	RED	+5V	
5	BLACK	GND	
6	RED	+5V	
7	BLACK	GND	
8	GRAY	P/L	
9	PURPLE	+5VSB	
10	YELLOW	+12V1	
11	YELLOW	+12V1	
12	ORANGE	+3.3V	
13	ORANGE	+3.3V	
13-1	ORANGE	+3.3V POWER 22#	
14	BLU	-12V	
15	BLACK	GND	
16	GREEN	P5-DN	
17	BLACK	GND	
18	BLACK	GND	
19	BLACK	GND	
20	GREEN	N/C	
21	RED	+5V	
22	RED	-5V	
23	RED	-5V	
24	BLACK	GND	

Model		TC-350PD1		iStarUSA™	
Title					
Drawn	YCX	Date	2005/03/01	Projection	1st Angle
Checked		Approved		Rev.	A2
spec.				Unit	mm
PIN				Quantity	
				Remarks	