

iStarUSA™

Industrial Backplane Specifications

PD-IMG206-0

PICMG PCISA backplane specification:

1. Support 2 sets PICMG (PCI+ISA) connector
2. Support 3 slots PCI 32 bit connector
3. Support 3 slots ISA connector
4. Support 2 pcs 5 pin connector for AT keyboard
5. Support 2 pcs 3 pin for DC-12V connectors
6. Support 5 pcs power LED for +12V, +3.3V, +5V, -12V, -5V
7. Support 1 pcs AT 12 pin power DC in connector
8. Support 1 pcs ATX 20 pin DC in power connector
9. Support 1 pcs 4 pin ATX power control connector

PD-IMG212-0

PICMG V1.0RC1.0 backplane feature set:

1. Support PICMG ver. 1.0RC1.0 SHB slot X 2
2. Support PCI 32 bit 5V slots X 4
3. Support ISA slots X 8
4. Support ATX/BTX 24P power connector X 1
5. Support P8.P9 12P power connector X 1

PD-IMG104-3

PICMG V1.3RC1.0 backplane feature set:

1. Support PICMG ver 1.3RC1.0 SHB slot X 1
2. Support PCI-E 16X slot X 1
3. Support PCI-E 1X slot X 1
4. Support PCI 32 bit 5V slots X 2
5. Support USB ports X 2
6. Support SATA connectors X 2
7. Support ATX/BTX 24P power connector X 1
8. Support 3 pin fan connectors X 4
9. Support +5V, +12V, +3.3V, +5VSB, -12V power LED

PD-IIA014

PICMG V1.0RC1.0 backplane feature set:

1. Support ISA slots X 14
2. Support P8 、 P9 12P power connector X 1
3. Support ATX/BTX 24P power connector X 1
4. Support +5V, +12V, +3.3V, +5VSB, -12V power LED